



Lubrita Go Life FE SAE 0W-20

Fully synthetic smooth-running engine oil

NS-PVL-4005
Passenger vehicle engine oils

Product Description and Benefits

Lubrita Go Life FE SAE 0W-20 is a fully synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

Lubrita Go Life FE SAE 0W-20 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions. Properties:

- Excellent cold starting properties, even at low temperatures
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Application

Lubrita Go Life FE SAE 0W-20 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. It therefore reduces the CO2 emissions and contributions to the protection of the environment.

Lubrita Go Life FE SAE 0W-20 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Lubrita Go Life FE SAE 0W-20 meets the following performance specifications:

ACEA A1/B1, A5/B5; API SN; ILSAC GF-5

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/m³	841
Viscosity 100 °C	mm²/s	8,0
Viscosity Index		158
Pour Point	°C	-63

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidaries.

More information available: TDS revised date: 2015 03 13

web page: www.lubrita.com e-mail: info@lubrita.com