



## Lubrita Go Life SAE 5W-40

Fully synthetic smooth-running engine oil

*ST-PVL-4018*

*Passenger vehicle engine oils*

### Product Description and Benefits

Lubrita Go Life SAE 5W-40 is a fully synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Lubrita Go Life SAE 5W-40 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear.

With Lubrita Go Life SAE 5W-40, a reliable and heavy-duty engine oil has been developed to guarantee the low viscosity of SAE 5W-class as well as a low evaporation loss. Extended oil change intervals as per manufacturer's instructions.

Properties:

- Excellent cold starting properties, even at low temperatures below -30°C.
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources

### Application

Lubrita Go Life SAE 5W-40 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

Lubrita Go Life SAE 5W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

### Lubrita Go Life SAE 5W-40 meets the following performance specifications:

ACEA A3/B4; API SN/CF; MB 229.3; API SN; Porsche A40 from 1973 (except Cayenne V6); VW502 00/505 00; BMW Longlife-98; RENAULT RN0700, RN 0710; Opel GM-LL-B-025.

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/m <sup>3</sup>	853
Viscosity 100 °C	mm <sup>2</sup> /s	14.0
Viscosity Index		167
Pour Point	°C	-40

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of its subsidiaries.