



Lubrita Eco Life C2 SAE 5W-20

A fuel economy, universal motor oil

NS-PVL-4009

Passenger vehicle engine oils

Product Description and Benefits

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Lubrita Eco Life C2 SAE 5W-20 meets the following performance specifications:

API SN/CF; ACEA C2

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,848
Viscosity -30 °C	mPa.s	6010
Viscosity 40 °C	mm ² /s	40,60
Viscosity 100 °C	mm ² /s	7,95
Viscosity Index		172
Flash Point COC	°C	228
Pour Point	°C	-39
Total Base Number	mgKOH/g	7,3

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of Lubrita Europe B.V. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com