



Lubrita Eco Life C1 SAE 5W-30

NS-PVL-4010

A fuel economy, universal motor oil

Passenger vehicle engine oils

Product Description and Benefits

Fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated.

- a lower fuel consumption
- suitable for modern catalysts
- low combustion ash building (low SAPS)
- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

Universal, fuel economy, specially composed motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and deliveryvans. Due to its special composition this product can be applied in vehicles with modernthree way catalysts and diesel particle filters. Due to its low SAPS content this motor oilcontributes to the extension of the lifetime of particle filters for diesel engines.

Warning: These oils have the lowest SAPS limits and may be unsuitable for use insome engines.

Lubrita Eco Life C1 SAE 5W-30 meets the following performance specifications:

ACEA C1; Ford WSS-M2C934-B; Jaguar Land Rover STJR.03.5005

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,849
Viscosity -30 °C	mPa.s	3900
Viscosity 40 °C	mm²/s	52,50
Viscosity 100 °C	mm²/s	9,46
Viscosity Index		166
Flash Point COC	°C	224
Pour Point	°C	-39
Total Base Number	mgKOH/g	6,2
Sulphate Ash	%	0,49

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidaries.

More information available: TDS revised date: 2014 10 30

web page: www.lubrita.com e-mail: info@lubrita.com