



Lubrita Eco Life C2 SAE 5W-30

A fuel economy, universal motor oil

NS-PVL-4011

Passenger vehicle engine oils

Product Description and Benefits

A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal, fuel economy, low SAPS motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Lubrita Eco Life C2 SAE 5W-30 meets the following performance specifications:

API SN/CF; ACEA C2; Renault RN0700; Fiat 9.55535-S1

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,853
Viscosity -30 °C	mPa.s	5550
Viscosity 40 °C	mm ² /s	61,70
Viscosity 100 °C	mm ² /s	10,50
Viscosity Index		160
Flash Point COC	°C	236
Pour Point	°C	-45
Total Base Number	mgKOH/g	7,7
Sulphate Ash	%	0,76

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of its subsidiaries.