



## Lubrita Eco Life C3 DX2 SAE 5W-30

Fully synthetic Low SAPS smooth running engine oil

ST-PVL-4017

*Passenger vehicle engine oils*

### Product Description and Benefits

Lubrita Eco Life C3 DX2 SAE 5W-30 is a synthetic Low SAPS smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

Lubrita Eco Life C3 DX2 SAE 5W-30 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear.

Lubrita Eco Life C3 DX2 SAE 5W-30, a reliable and heavy-duty engine oil has been developed to guarantee the low viscosity of SAPS 5W-class as well as a low evaporation loss. Extended oil change intervals as per manufacturer's instructions

### Properties

- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- Excellent cold starting properties
- LowSAPS = low sulphated ash, phosphorous and sulphur

### Application

Lubrita Eco Life C3 DX2 SAE 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

Lubrita Eco Life C3 DX2 SAE 5W-30 can be used in engines with the specifications indicated.

The operating instructions of the automobile and engine manufacturer must be observed.

### Lubrita Eco Life C3 DX2 SAE 5W-30 meets the following performance specifications:

API SN/SM/CF, ACEA C3

MB-APPROVAL 229.52

MB 229.51, BMW Longlife -04, GM Dexos 2

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,85
Viscosity 40 °C	mm <sup>2</sup> /s	72,90
Viscosity 100 °C	mm <sup>2</sup> /s	12,20
Viscosity Index		166
Pour Point	°C	-39

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of Lubrita Europe B.V. or one of its subsidiaries.

More information available:

TDS revise date: 2018.07.11

web page: [www.lubrita.com](http://www.lubrita.com)

e-mail: [info@lubrita.com](mailto:info@lubrita.com)