



Lubrita Eco Life C3 SAE 5W-40

Fully synthetic Mid SAPS smooth-running engine oil

ST-PVL-4019

Passenger vehicle engine oils

Product Description and Benefits

Lubrita Eco Life C3 SAE 5W-40 is a fully synthetic Mid SAPS smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

Lubrita Eco Life C3 SAE 5W-40 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Thanks to its formulation with special base oils,

Lubrita Eco Life C3 SAE 5W-40 achieves a high viscosity index. The excellent cold starting performance ensures optimum lubrication reliability in the cold-running phase. Thanks to significant fuel savings and the reduction of emissions, Lubrita Eco Life C3 SAE 5W-40 contributes to the protection of the environment. Extended oil change intervals as per manufacturer's instructions.

Properties:

- Excellent cold starting properties, even at low temperatures below -30°
- The function of the hydraulic valve lifter is guaranteed at all temperatures
- Fuel savings under all operating conditions
- A secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- MID SAPS = reduced sulphated ash, phosphorous and sulphur

Application

Lubrita Eco Life C3 SAE 5W-40 is a universal, synthetic smooth-running engine oil, which has been developed especially for pump-nozzle diesel engines.

Lubrita Eco Life C3 SAE 5W-40 is suitable for petrol and diesel engines in cars and transporters with and without turbochargers.

Lubrita Eco Life C3 SAE 5W-40 meets the following performance specifications:

API SN/CF ACEA C3 MB 229.31 VW 505 00 / 502 00 / 505 01 Porsche A40 BMW Longlife-04 Ford WSS-M2C917-A GM Dexos2 Renault RN0700 / RN0710 MB 229.51 Fiat 9.55535-S2

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/m ³	853
Viscosity 100 °C	mm ² /s	13.8
Viscosity Index		166
Pour Point	°C	-45

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of its subsidiaries.