



# **Lubrita Special Long Life GM SAE 5W-30**

Synthetic, fuel economy, universal motor oil

ST-PVL-4014
Passenger vehicle engine oils

#### **Product Description and Benefits**

An extreme modern, synthetic, fuel economy, universal motor oil, produced with specialselected base oils with a high viscosity index and a well balanced choice of advancedadditives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- flexibel oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### **Application**

This special composed, universal, fuel economy motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and deliveryvans with flexible oil drain intervals. Due to its special composition is this productextremely suitable for Opel GM-LL-A-025/B-025.

## Lubrita Special Long Life GM SAE 5W-30 meets the following performance specifications:

ACEA A3/B4; API SL/CF; GM LL-A-025/LL-B-025

#### **Typical Analysis**

Property	Unit	Typical Value
Density at 15°C	kg/l	0,854
Viscosity -30 °C	mPa.s	5960
Viscosity 40 °C	mm²/s	70,10
Viscosity 100 °C	mm²/s	11,70
Viscosity Index		163
Flash Point COC	°C	242
Pour Point	°C	-40
Total Base Number	mgKOH/g	11,1
Sulphate Ash	%	1,41

#### **Health and Safety**

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidaries.