



# Lubrita Pro Life SM SAE 10W-40

ST-PVL-4021

Semi-synthetic high-per ormance, smooth-running engine oil

Passenger vehicle engine oils

#### **Product Description and Ben fit**

Lubrita Pro Life SM SAE 10W-40 is a semi-synthetic high-performance, smooth-running engine oil for carburet-tor and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions.

Lubrita Pro Life SM SAE 10W-40 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear.

With Lubrita Pro Life SM SAE 10W-40, a reliable and heavy-duty engine oil has been developed. Properties

- Excellent cold starting p operties, ven at low temperatures below -25°
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating ondition
- Very good detergent and dispersing propertie
- Neutrality towards sealants
- Low evaporation, thus I w oil consumptio
- Extensive protection a ainst wear, corrosion and foaming.
- Suitable for catalytic onverters
- Extended oil change intervals protect natural resources

#### **Applicatio**

Lubrita Pro Life SM SAE 10W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

Lubrita Pro Life SM SAE 10W-40 can be used in engines with the specifications indicated. The operating in-structions of the automobile and engine manufacturer must be observed.

## Lubrita Pro Life SM SAE 10W-40 meets the following performance specifications:

API SM/CF; ACEA A3/B4; MB 229.1; BMW Special Oil; VW 501 01 / 505 00

### **Typical Analysis**

Property	Unit	Typical Value
Density at 15°C	kg/m³	866
Viscosity 100 °C	mm²/s	13.7
Viscosity Index		156
Pour Point	°C	-36

### Health and Safety

Based on available information, this product is not expected to produce adverse eAects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidaries.

More information vailable: *TDS revised date: 2015 03 13* 

web page: www.lubrita.com e-mail: info@lubrita.com