



Lubrita Premium SG SAE 15W-40

A multifunctional motor oil

ST-PVL-4026

Passenger vehicle engine oils

Product Description and Benefits

A multifunctional motor oil, produced with high quality solvent refined base oils and additives to obtain the following properties:

- a very strong detergency and dispersion power
- a very strong resistance against oxidation
- a very strong protection against wear
- an excellent protection against corrosion and foaming
- a high and stable viscosity index
- no negative effect on exhaust gas catalyst

Application

A multifunctional motor oil, recommended for use in petrol -, diesel -, and LPG -engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Lubrita Premium SG SAE 15W-40 meets the following performance specifications:

API SG/CD; CCMC G4

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,878
Viscosity -20 °C	mPa.s	6300
Viscosity 40 °C	mm ² /s	101,40
Viscosity 100 °C	mm ² /s	13,80
Viscosity Index		137
Flash Point COC	°C	220
Pour Point	°C	-26
Total Base Number	mgKOH/g	6,3
Sulphate Ash	%	0,84

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of its subsidiaries.