



Lubrita DEO EHPX GLOBAL 10W-40

A top quality fuel economy diesel engine oil

ST-CVL-4036

Heavy duty diesel engine oils

Product Description and Benefits

A top quality fuel economy diesel engine oil based on the latest additive technology combined with very special base oils. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against wear, corrosion and foam
- a high and stable viscosity index
- a low sulphated ash number
- prolonged oil drain intervals
- a lower fuel consumption

Application

This fuel saving lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for EURO 4 and EURO 5 engines without particle filter and for most engines with exhaust gas emission systems. This engine oil is also developed to (in consideration of the official instructions) allow very long extended oil drain intervals and to prevent "bore-polishing".

Lubrita DEO EHPX GLOBAL 10W-40 meets the following performance specifications:

API CI-4	ACEA E4/E7	MB-Approval 228.5	MAN 3277	
Meets the requirements of	Volvo VDS-3	Renault RXD/RLD-2	MTU III	Deutz III-05
Mack EO-M+	Cummins 20078	Global DHD-1	Detroit Diesel 93K215	CAT ECF-2

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,866
Viscosity -25 °C	mPa.s	6800
Viscosity 40 °C	mm ² /s	101,40
Viscosity 100 °C	mm ² /s	14,60
Viscosity Index		149
Flash Point COC	°C	226
Pour Point	°C	-39
Total Base Number	mgKOH/g	12,6
Sulphate Ash	%	1,48

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com