



Lubrita DEO UHPX ECO 10W-40

A top quality fuel economy diesel engine oil

ST-CVL-4037

Heavy duty diesel engine oils

Product Description and Benefits

Lubrita DEO UHPX ECO 10W-40 is a universal engine oil on a basis of selected base oils combined with the latest additives for all diesel engines with or without turbocharging in lorries, buses and machinery.

Lubrita DEO UHPX ECO 10W-40 was developed as a UHPD (Ultra High Performance Diesel) engine oil with specific requirements on the diesel particulate filter for LOW SPAsh technology. Low sulphur, phosphorus and ash content.

This engine oil has the following properties:

- Excellent oxidation stability
- Very good high-temperature stability
- Excellent detergent and dispersant properties
- Efficiency due to low fuel consumption
- Excellent cold starting performance; a fast engine lubrication even at low temperatures
- Very good viscosity and temperature behaviour
- Neutrality towards sealants
- High wear protection

Application

Lubrita DEO UHPX ECO 10W-40 is a high-performance engine oil suitable for year-round use. It was designed for the new exhaust emission guidelines including for vehicles with exhaust gas recirculation systems.

Lubrita DEO UHPX ECO 10W-40 is universally applicable in all diesel engines with and without turbocharging. Suitable for EURO I, II, III, IV, V and EURO VI engines.

Lubrita DEO UHPX ECO 10W-40 meets the following performance specifications:

ACEA E7/E6/E4 API CI-4 MB 228.51 VOLVO VDS-3 Renault VI RLD-2 Mack EO-N MAN M 3477
Deutz DQC-III-10LA MAN M 3277 MB 226.9 MTU Type 3 MTU Type 3.1 Renault RXD Scania LDF
DAF HP-2 Cummins CES 20076/77 JASO DH-2

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,863
Viscosity 100 °C	mm ² /s	13,20
Viscosity Index		159
Pour Point	°C	-39

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com