



Lubrita DEO Super Fleet CI-4/SL

Modern, universal applicable engine oil

NS-CVL-4043

Heavy duty diesel engine oils

Product Description and Benefits

This modern, universal applicable engine oil is produced with high quality solvent refined base oils and a well-balanced choice of additives. This multigrade engine oil has the following properties:

- a very good detergency prevents deposits in the engine
- a very good dispersion that prevents from precipitation and sludge
- a powerful action against corrosion and foam
- a high and stable viscosity index
- a low sulphated ash content
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application

This universal engine oil is suitable for the lubrication of gasoline and diesel engines, with or without turbo-loading, under heavy operating conditions and all the year round. This oil is excellent suitable for mixed fleets and can be applied in e.g. EURO 3 and EURO 4 engines. Due to its special composition longer drain intervals are possible with this motor oil.

Lubrita DEO Super Fleet CI-4/SL meets the following performance specifications:

API CI-4/SL

ACEA A3/B3/E5/E7

Meets the requirements of

MB 228.3/229.1

CAT ECF-1-a

CUMMINS 20071,20072,20076,20077,20078

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,883
Viscosity -20 °C	mPa.s	6500
Viscosity 40 °C	mm ² /s	101,50
Viscosity 100 °C	mm ² /s	14,40
Viscosity Index		146
Flash Point COC	°C	212
Pour Point	°C	-36
Total Base Number	mgKOH/g	8,3
Sulphate Ash	%	1,08

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com