



## Lubrita UTTO HTF

Universal hydraulic and transmission oil

**ST-AGR-4066**  
**Agricultural oils**

### Product Description and Benefits

A nowadays universal hydraulic and transmission oil formulated with solvent refined base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefore applicable in systems with “wet” brakes
- excellent corrosion and foam preventing properties

### Application

This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

### Lubrita UTTO HTF meets the following performance specifications:

Ford M2C134-D      MF M-1141/M-1143      Caterpillar TO-2; John Deere JDM 20A/C      API GL-4  
API GL-4      Case MS1206, MS1207      Case MAT 3505/MS 1209 suitable for use

### Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,882
Viscosity 40 °C	mm <sup>2</sup> /s	56,10
Viscosity 100 °C	mm <sup>2</sup> /s	9,05
Viscosity Index		141
Flash Point COC	°C	225
Pour Point	°C	-35
Total Base Number	mgKOH/g	7,3
Sulphate Ash	%	1,19

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)