



## Lubrita HD Gear Oil 80W-90

Mineral lubricating oil for mechanical transmissions

**NS-AGO-4080**

*Automotive gear oils*

### Product Description and Benefits

This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:

- excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties

### Application

This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.

**Lubrita HD Gear Oil 80W-90 meets the following performance specifications:**

API GL-5

### Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,893
Viscosity 40 °C	mm <sup>2</sup> /s	150,50
Viscosity 100 °C	mm <sup>2</sup> /s	15,20
Viscosity Index		102
Flash Point COC	°C	214
Pour Point	°C	-27

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)