



Lubrita HDS Gear Oil LS 75W-90

Semi-synthetic lubricating oil for mechanical transmissions

NS-AGO-4083

Automotive gear oils

Product Description and Benefits

This is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality solvent refined and synthetic base oils and special EP-additives to obtain the following properties:

- an excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a very low pour point
- very good EP-properties
- excellent "Limited Slip" properties
- fuel economy

Application

This gear oil has especially been developed for the perfect lubrication of so-called "Limited Slip" and "Auto-Locking" hypoid transmissions.

Lubrita HDS Gear Oil LS 75W-90 meets the following performance specifications:

API GL-5 Mil-L-2105D ZF TE-ML 05C (suitable for use)

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,874
Viscosity 40 °C	mm ² /s	78,80
Viscosity 100 °C	mm ² /s	14,40
Viscosity Index		192
Flash Point COC	°C	172
Pour Point	°C	-45

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com