



Lubrita MTS Gear Oil 75W-80

Universal, mineral multigrade lubricating oil

ST-AGO-4084

Automotive gear oils

Product Description and Benefits

This transmission oil is an universal, mineral multigrade lubricating oil for mechanical transmissions, with EP-properties. Due to the addition of high quality solvent refined base oils and special additives this gear oil has the following properties:

- a very high activity against wear, corrosion and foam
- an excellent resistance against oxidation
- low viscosity at low temperatures
- very good EP-properties
- a high and stable viscosity index

Application

This special transmission oil is used in gearboxes where a good clutch-switch performance is necessary. This gear oil can also be used where the manufacturer of the gearbox prescribes a gear oil with a low viscosity.

Lubrita MTS Gear Oil 75W-80 meets the following performance specifications:

API GL-4*+* Mil-L-2105 Citroën

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,888
Viscosity -40 °C	mPa.s	120000
Viscosity 40 °C	mm ² /s	50,80
Viscosity 100 °C	mm ² /s	8,57
Viscosity Index		146
Flash Point COC	°C	170
Pour Point	°C	-40
Total Base Number	mgKOH/g	8,7
Sulphate Ash	%	1,34

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com