



Lubrita HDS Gear Oil 75W-90

Semi-synthetic lubricating oil for mechanical transmissions

ST-AGO-4085

Automotive gear oils

Product Description and Benefits

This gear oil is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality solvent refined and synthetic base oils and special EP-additives to obtain the following properties:

- excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties
- fuel economy

Application

This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.

Lubrita HDS Gear Oil 75W-90 meets the following performance specifications:

API GL-5 Mil-L-2105D ZF TE-ML-05A/07A/17B CS 3000B Ford M2C9002-A Mack GO-G GM

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,873
Viscosity 40 °C	mm ² /s	80,90
Viscosity 100 °C	mm ² /s	14,80
Viscosity Index		192
Flash Point COC	°C	190
Pour Point	°C	-45

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com