



Lubrita Unitrans Gear Oil LS 75W-90

Full-synthetic lubricating oil for mechanical transmissions

NS-AGO-4087

Automotive gear oils

Product Description and Benefits

This gear oil is a full-synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties
- excellent "Limited Slip" properties
- good clutch-switch performance at low temperatures
- fuel economy

Application

This gear oil is used in gearboxes under very heavy-duty conditions and should be used in all gearboxes where mineral EP-gear oils give switch problems. This product also contains excellent "Limited Slip" properties.

Lubrita Unitrans Gear Oil LS 75W-90 meets the following performance specifications:

API GL-4/5 MIL-L-2105

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,855
Viscosity 40 °C	mm ² /s	74,30
Viscosity 100 °C	mm ² /s	14,40
Viscosity Index		202
Flash Point COC	°C	165
Pour Point	°C	-43

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com