



Lubrita Unitrans S Gear Oil 80W-90

Universal semi-synthetic gear oil

ST-AGO-4093

Automotive gear oils

Product Description and Benefits

This gear oil is a universal semi-synthetic gear oil based on high quality solvent refined and synthetic base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special EP-properties
- widely usable

Application

This is a universal gear oil, special developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product very widely usable.

Lubrita Unitrans S Gear Oil 80W-90 meets the following performance specifications:

API GL-3/GL-4/GL-5/MT-1 MIL-L-2105A/B/C/D/E Meets the requirements of MAN 341 Type E-2/3343 Type M Scania 1:0
Volvo 97310 ZF TE-ML-02B/05A/07A/08A/12E ZF TE-ML-16B/16C/16D/17B/19B/21A
MB 235.0

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,883
Viscosity 40 °C	mm ² /s	125,80
Viscosity 100 °C	mm ² /s	15,00
Viscosity Index		122
Flash Point COC	°C	234
Pour Point	°C	-35

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com