



Lubrita Unitrans Gear Oil LS 85W-140

Universal gear oil

NS-AGO-4097

Automotive gear oils

Product Description and Benefits

This gear oil is an universal gear oil based on high quality solvent refined base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- an excellent activity against wear, corrosion and foam
- very special EP-properties
- excellent "Limited Slip" properties
- widely usable

Application

This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable. This product also contains excellent "Limited Slip" properties.

Lubrita Unitrans Gear Oil LS 85W-140 meets the following performance specifications:

API GL-3/GL-4/GL-5 MIL-L-2105A/B/C/D/E Meets the requirements of
 MAN 341 Type Z-2/342 Type M-2/3343 Type S Scania 1:0 Volvo 97310
 ZF TE-ML-05C/07A/08A/12C/16E/17B

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,905
Viscosity 40 °C	mm ² /s	345,80
Viscosity 100 °C	mm ² /s	26,10
Viscosity Index		99
Flash Point COC	°C	222
Pour Point	°C	-18

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
 e-mail: info@lubrita.com