



## Lubrita GL-1 Gear Oil 80W

Mineral lubricating oil for mechanical transmissions

**NS-AGO-4102**

*Automotive gear oils*

### Product Description and Benefits

This gear oil is a mineral lubricating oil for mechanical transmissions. This lubricant is very stable against oxidation and protects from corrosion and foam formation.

### Application

This gear oil is used in gearboxes, differentials, steering boxes and other transmissions for which the manufacturer not prescribes or even refuses a mineral lubricant with EP-additives.

**Lubrita GL-1 Gear Oil 80W meets the following performance specifications:**

API GL-1

### Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,874
Viscosity 40 °C	mm <sup>2</sup> /s	64,00
Viscosity 100 °C	mm <sup>2</sup> /s	8,30
Viscosity Index		98
Flash Point COC	°C	215
Pour Point	°C	-25

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)