



Lubrita GL-4 Gear Oil 140

Mineral lubricating oil for mechanical transmissions

NS-AGO-4106

Automotive gear oils

Product Description and Benefits

This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high-quality solvent refined base oils and special EP-additives to obtain the following properties:

- a good resistance against oxidation
- good rust-preventing, anti-corrosion and foam inhibiting properties
- a low pourpoint
- good Extreme Pressure (EP) properties

Application

This gear oil should be used in hypoid differentials, gearboxes and other transmissions, for which an EP-transmission oil is advised.

Lubrita GL-4 Gear Oil 140 meets the following performance specifications:

API GL-4 Mil-L-2105 CS 3000 Ford M2C9008-A GM

Typical Analysis

| Property | Unit | Typical Value |
|------------------|--------------------|---------------|
| Density @15°C | kg/ | 0,903 |
| Viscosity 40 °C | mm ² /s | 429,00 |
| Viscosity 100 °C | mm ² /s | 29,00 |
| Viscosity Index | | 95 |
| Flash Point COC | °C | 244 |
| Pour Point | °C | -12 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com