



Lubrita GL-5 Gear Oil 90

Mineral lubricating oil for mechanical transmissions

NS-AGO-4107

Automotive gear oils

Product Description and Benefits

This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:

- excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties

Application

This gear oil is used in hypoid differentials under very heavy-duty conditions and should be used in all transmissions that require EP-transmission oils.

Lubrita GL-5 Gear Oil 90 meets the following performance specifications:

API GL-5	Mil-L-2105D	CS 3000B	Ford M2C9002-A	MB-Approval 235.0
GM	Meets the requirements of	MAN 342 Type M-1	ZF TE-ML-05A/07A/16B/17B	Mack GO-G

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,898
Viscosity 40 °C	mm ² /s	191,00
Viscosity 100 °C	mm ² /s	17,20
Viscosity Index		96
Flash Point COC	°C	230
Pour Point	°C	-15

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com