



Lubrita Dexron IID

Very high graded automatic transmission fluid

ST-ATF-4108

Automatic transmission fluids

Product Description and Benefits

Very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- high and stable viscosity index
- very low pour point
- very good stability against oxidation
- positive activity against wear, corrosion and foam
- specific friction properties
- perfect compatibility with seals and non-ferro metals
- red coloured

Application

This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

Lubrita Dexron IID meets the following performance specifications:

Allison C4, Cat TO-2, Ford Mercon/M2C138-CJ/166-H, GM Dexron IID, MAN 339 Typ Z1/V1, MB 236.6/236.7, Voith 55.6335 (G607), ZF TE-ML 09/11A/14A,

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,872
Viscosity 40 °C	mm ² /s	43,20
Viscosity 100 °C	mm ² /s	8,25
Viscosity Index		168
Flash Point COC	°C	198
Pour Point	°C	-45
Total Base Number	mgKOH/g	2,6
Sulphate Ash	%	0,18

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com