



Lubrita Dexron SX-VI

NS-ATF-4110

A very high graded automatic transmission fluid

Automatic transmission fluids

Product Description and Benefits

A very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- longer life time of the liquid
- exceeds the properties of Dexron III and II liquids
- red coloured

Application

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types.

Lubrita Dexron SX-VI meets the following performance specifications:

Meets the level of

Dexron VI (level) MB 236.41

Typical Analysis

Property	Unit	Typical Value
Colour		ROOD
Density @15°C	kg/	0,847
Viscosity 40 °C	mm²/s	29,80
Viscosity 100 °C	mm²/s	6,00
Viscosity Index		151
Flash Point PM	°C	180
Flash Point COC	°C	206
Pour Point	°C	-54
Total Base Number	mgKOH/g	2,0
Sulphate Ash	%	0,02

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidaries.

More information available: e-mail: info@lubrita.com