



## Lubrita ATF 7G

A very high graded automatic transmission fluid

**ST-ATF-4111**

**Automatic transmission fluids**

### Product Description and Benefit

A very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability over lifetime ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- red coloured

### Application

This fluid may be used for automatic transmissions of different car manufacturers.

### Lubrita ATF 7G meets the following performance specifications:

Allison C4/TES-389, Chrysler ATF+/+2/+3/+4, Ford Mercon V/Mercon/WSS-M2C922-A1, GM Dexron II/IIID/IIIE/IIIG/IIIH, Honda ATF-Z1 (except in CVT), Hyundai/Kia SP-II/SP-III, Isuzu ATF II/III, Jaguar JLM 20238/20292/21044, JASO M315 Type 1A, Mazda M-III/Type T-IV, JWS 3309, MB 236.3/236.5/236.6/236.7/236.8, MB 236.9/236.10/236.11/236.91, Mitsubishi SP-II/SP-III/ATF J-2, Nissan Matic D/J/K/W, Subaru ATF HP, Suzuki ATF 3314/3317, Toyota Type DII/T/T-III/T-IV, VAG G-052-025/052-055/052-162/052-990/055-025, Volvo 1161540, ZF TE-ML 11A/11B

### Typical Analysis

Property	Unit	Typical Value
Colour		ROOD
Density at 15°C	kg/l	0,855
Viscosity -30 °C	mm <sup>2</sup> /s	2980
Viscosity 40 °C	mm <sup>2</sup> /s	33,10
Viscosity 100 °C	mm <sup>2</sup> /s	7,10
Viscosity Index		185
Flash Point COC	°C	200
Pour Point	°C	-54

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of Lubrita Europe B.V. or one of its subsidiaries.