



## Lubrita ATF Dexron III SP-JP

Synthetic automatic transmission fluid

**NS-ATF-4113**

*Automatic transmission fluids*

### Product Description and Benefits

A synthetic automatic transmission fluid formulated with a number of special additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and consequently low noise
- suitable for Japanese automatic transmissions
- a quick oil provision at cold start conditions

### Application

This fluid may be used for automatic gear boxes, torque converters and other equipment of Japanese OEM's, for which an ATF Dexron IIIG fluid is required.

### Lubrita ATF Dexron III SP-JP meets the following performance specifications:

Dexron III (level)	Allison C-4 (level)	Jaso 1A
Nissan (level)	Subaru	Toyota (T-4 ATF's)

### Typical Analysis

Property	Unit	Typical Value
Colour		ROOD
Density @15°C	kg/	0,860
Viscosity 40 °C	mm <sup>2</sup> /s	33,00
Viscosity 100 °C	mm <sup>2</sup> /s	6,50
Flash Point COC	°C	186
Pour Point	°C	-40
Acid number	mgKOH/g	1,73

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)