



Lubrita ATF Ford

High grade automatic transmission fluid

NS-ATF-4114

Automatic transmission fluids

Product Description and Benefits

A high grade automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red colour

Application

Applicable for all automatic transmissions, power steering units and torque converters, for which an ATF type Ford is required.

Lubrita ATF Ford meets the following performance specifications:

Ford M2C33-F/G

Borg Warner

Ford M2C9007-AA

Typical Analysis

Property	Unit	Typical Value
Colour		ROOD
Density @15°C	kg/	0,872
Viscosity 40 °C	mm ² /s	34,90
Viscosity 100 °C	mm ² /s	7,21
Viscosity Index		177
Flash Point COC	°C	195
Pour Point	°C	-41
Total Base Number	mgKOH/g	1,0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com