



Lubrita MCVTF

High performance synthetic fluid

ST-ATF-4115

Automatic transmission fluids

Product Description and Benefits

A high performance synthetic fluid for modern continuously variable transmissions, based on synthetic base oils, formulated with special additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- ideal friction performance, for both CVT belt and CVT chain
- seal compatibility for better leakage prevention
- high superior anti-shudder performance
- extended service interval in combination with a longer transmission life

Application

This high quality synthetic fluid is designed for application in continuously variable automatic gear boxes. The so called CVT's.

Lubrita MCVTF meets the following performance specifications:

Meets the requirements of
 Subaru ECVT/iCVT, Daihatsu Ammix CVT
 Mini Cooper EZL799
 Toyota CVTF TC/FE, Nissan NS-1/ NS-2
 Suzuki CVTF TC/NS-2/CVT Green 1
 Honda HMMF/HCF2, Mitsubishi SP-III/CVTF-J1
 Hyundai SP-III, Chrysler Jeep NS-2

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,848
Viscosity 40 °C	mm ² /s	38,00
Viscosity 100 °C	mm ² /s	181
Flash Point COC	°C	214
Pour Point	°C	-48
Total Base Number	mgKOH/g	3,6

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
 e-mail: info@lubrita.com