



Lubrita PSF

Special hydraulic fluid

NS-ATF-4117

Automatic transmission fluids

Product Description and Benefits

This is a special hydraulic fluid based on very special advanced base oils to which special additives have been added in order to obtain the following unique properties:

- a exceptional high viscosity index (>300!), obtaining a very positive viscosity development
- a very low pour point
- very strong anti-foaming properties
- a good compatibility with seals

Application

This special hydraulic fluid is used as a hydraulic agent in very different hydraulic systems, such as power steering systems, leveling systems, hydraulic pneumatic spring systems, shock absorbing devices, hydrostatic driving gears, ABS/ASR and ASC systems, hydraulically controlled couplings and electro-hydraulic folding roof control systems, etc.

Lubrita PSF meets the following performance specifications:

VW TL 52146 (level)

Peugeot S712710 (level)

Volvo STD 1273,36 (level)

DIN 51524, T3

ISO 7308, MAN M3289 (level)

Typical Analysis

Property	Unit	Typical Value
Colour		GROEN
Density @15°C	kg/	0,829
Viscosity -20 °C	mm ² /s	230
Viscosity 40 °C	mm ² /s	18,70
Viscosity 100 °C	mm ² /s	6,00
Viscosity Index		> 300
Flash Point COC	°C	154
Pour Point	°C	-55

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com