



## Lubrita LHM

Special type of hydraulic fluid

**ST-ATF-4118**

*Automatic transmission fluids*

### Product Description and Benefits

A special type of hydraulic fluid, based on selected base-oils and additives to obtain the following properties:

- an extremely high and stable viscosity index
- a very low pour point
- a neutral behaviour towards oil-proof seals
- strong foam-inhibiting properties
- not hygroscopic

### Application

This hydraulic oil has been especially developed for application in brake systems and hydraulic controlled clutches in a number of Citroën cars. Also suitable for certain industrial hydraulic systems, where anti-wear properties are required.

**Lubrita LHM meets the following performance specifications:**

Citroën

### Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,840
Viscosity -40 °C	mm <sup>2</sup> /s	1150
Viscosity 40 °C	mm <sup>2</sup> /s	18,00
Viscosity 100 °C	mm <sup>2</sup> /s	6,30
Viscosity Index		353
Flash Point COC	°C	105
Pour Point	°C	<-60
Acid number	mgKOH/g	0,05
Anilinepoint	°C	95

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)