Technical Data Sheet



Lubrita Vacuumpump Oil SAE 10W30

High-grade vacuumpump oil

Product Description and Benefits

lubrita

lubricants

A high-grade vacuumpump oil based upon selected, solvent-refined base oils having a high viscosity index, under addition of additives to obtain the following properties:

- an excellent protection against wear
- a very good activity against rust and corrosion
- excellent stability against oxidation
- very good demulsification properties
- very good deaerating and foam-suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- a low pourpoint

Application

This oil may be used for lubricating vacuumpumps, where at least a HLP oil is prescribed, for both the gear box as well as for spray lubrication. This lubricant is also very suitable for use in milking-machines. This vacuumpump oil is a multigrade oil, which is very suitable for the lubrication the gearboxes of vacuumpumps.

Lubrita Vacuumpump Oil SAE 10W30 meets the following performance specifications:

DIN 51524, 2 HLPD

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/l	0,873
Viscosity -25 °C	mPa.s	6800
Viscosity 40 °C	mm²/s	72,00
Viscosity 100 °C	mm²/s	11,00
Viscosity Index		139
Flash Point COC	°C	205
Pour Point	°C	-32
Sulphate Ash	%	0,86

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidaries.

NS-VPO-4179 Vacuum pump oils