



## Lubrita Chain Saw Bio-Eco Oil 68

High quality chain-saw oil

**ST-BIOCSO-4199**

**Chain-saw oils**

### Product Description and Benefits

This is a chain-saw oil based upon total biodegradable natural ester oils under addition of special additives to obtain the tackiness and lubricity of the oil. The base oil of this biodegradable chain-saw oil and the special selected additives will be degraded by the environment in short time. Even at high temperatures this oil keeps a high grade of tackiness, preventing the oil to fling of the chain. Bio-Tack Eco 68 gives reduced harm for water and soil during use.

Bio-Tack Eco 68 contains a large fraction of bio-based material.

### Application

This product has been especially formulated to lubricate the chain, preventing the chain from overheating and loss of strength. **This chain-saw oil cannot be used for the lubrication of the engine of the saw.**

**Lubrita Chain Saw Bio-Eco Oil 68 meets the following performance specifications:**

ECOLABEL

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,918
Viscosity 40 °C	mm <sup>2</sup> /s	63,20
Viscosity 100 °C	mm <sup>2</sup> /s	14,30
Viscosity Index		238
Flash Point COC	°C	322
Pour Point	°C	-25

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)