



## Lubrita Spindle Oil 10

Pure naphtenic mineral oil

*NS-SPN-4204*

*Industrial Spindle oils*

### Product Description and Benefits

This is a pure naftenic mineral oil with a natural oxidation stability. This oil has a average viscosity index and contains no additives and has also a low percentage of aromatic hydrocarbons.

### Application

A lubricating oil for not loaded gearboxes and bearings. It is also suitable for general lubrication, especially suitable as lubricant in circulation systems, where an un-doped oil is asked or prescribed.

### Lubrita Spindle Oil 10 meets the following performance specifications:

(no data)

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,888
Viscosity 40 °C	mm <sup>2</sup> /s	9,10
Viscosity 100 °C	mm <sup>2</sup> /s	2,30
Flash Point COC	°C	146
Pour Point	°C	-57

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)