



Lubrita Moto 2T Kart and Racing

A full synthetic two stroke engine oil

NS-M2T-4242

Motocycles 2T oils

Product Description and Benefits

A full synthetic two stroke engine oil, formulated with carefully selected high quality synthetic base oils and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts.
- a very active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very strong activity against wear and corrosion.
- a very limited formation of smoke.
- self-mixing.

Application

This selfmixing two stroke engine oil is special advised for the lubrication of high speed two stroke engines under heavy duty load and specially suitable for us in kart- and racing motors.

Lubrita Moto 2T Kart and Racing meets the following performance specifications:

(no data)

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,910
Viscosity 40 °C	mm ² /s	92,20
Viscosity 100 °C	mm ² /s	13,50
Viscosity Index		148
Flash Point COC	°C	144
Pour Point	°C	-33
Total Base Number	mgKOH/g	1,5
Sulphate Ash	%	0,12

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com