



Lubrita Moto 4T Syn FS 20W-50

A new generation synthetic engine oil

NS-M4T-4229

Motocycles 4T oils

Product Description and Benefits

A new generation synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

Application

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

Lubrita Moto 4T Syn FS 20W-50 meets the following performance specifications:

Meets the requirements of JASO MA2

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,845
Viscosity -20 °C	mm ² /s	4000
Viscosity 40 °C	mm ² /s	111,30
Viscosity 100 °C	mm ² /s	17,10
Viscosity Index		168
Flash Point COC	°C	218
Pour Point	°C	-44
Total Base Number	mgKOH/g	7,7

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com