



Lubrita Moto 2T JASO

Two stroke engine oil

NS-M2T-4247

Motocycles 2T oils

Product Description and Benefits

A two stroke engine oil formulated with carefully selected high quality mineral and synthetic base oils and special two stroke additives, to achieve the following properties:

- a perfect lubrication of all motor parts
- an active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very effective activity against wear and corrosion
- a very limited formation of smoke
- selfmixing

Application

This two stroke engine oil is advised for the lubrication of high speed air cooled two stroke engines under heavy duty load. This selfmixing two stroke engine oil may also be used for watercooled two stroke engines (radiator type cooling systems).

Lubrita Moto 2T JASO meets the following performance specifications:

API TC

JASO FC

TISI

ISO-L-EGC

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,865
Viscosity 40 °C	mm ² /s	64,60
Viscosity 100 °C	mm ² /s	9,56
Viscosity Index		129
Flash Point COC	°C	116
Pour Point	°C	-20
Total Base Number	mgKOH/g	0,9
Sulphate Ash	%	0,09

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com