



Lubrita Fork Oil 5

Oil for motorcycle front forks

NS-FOR-4248

Motorcycles Fork oils

Product Description and Benefits

This oil for front forks is based on carefully selected base oils, to which a number of additives are added in order to obtain the following properties:

- a high and stable viscosity index
- excellent abrasion preventing properties
- very good corrosion preventing properties
- very good anti-foam and de-aerating properties
- neutral towards synthetic seals
- a low pour point

Application

This is an universal oil for use in front forks from motor-cycles and other shock absorbing systems in off road, street and racing engines.

Lubrita Fork Oil 5 Extra meets the following performance specifications:

(no data)

Typical Analysis

| Property | Unit | Typical Value |
|------------------|--------------------|---------------|
| Density at 15°C | kg/l | 0,882 |
| Viscosity 20 °C | mm ² /s | 49,60 |
| Viscosity 40 °C | mm ² /s | 22,50 |
| Viscosity 100 °C | mm ² /s | 5,07 |
| Viscosity Index | | 162 |
| Flash Point COC | °C | 174 |
| Pour Point | °C | -51 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com