



## Lubrita Marine HDC T8 SAE 30

Marine oil for diesel engines

NS-MAR-4258

Marine oils

### Product Description and Benefits

This marine oil for diesel engines in marine applications has the following properties:

- a strong oxidation stability
- a stable viscosity index
- a good alkalinity to neutralise the acid compounds, which are produced during the combustion of a distillate diesel fuel
- a high detergency and dispersion power
- effective in preventing from wear, corrosion and foam
- a low pourpoint
- a good water separation power

### Application

This marine oil is suitable for the system-lubrication of low-speed marine crosshead-type engines and other engines in coastal and inland navigation.

**Lubrita Marine HDC T8 SAE 30 meets the following performance specifications:**

API CC

MIL-L-2104A

DEF 2101D

FZG 8

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,891
Viscosity 40 °C	mm <sup>2</sup> /s	102,00
Viscosity 100 °C	mm <sup>2</sup> /s	11,50
Viscosity Index		99
Flash Point COC	°C	250
Pour Point	°C	-23
Total Base Number	mgKOH/g	8,3
Sulphate Ash	%	1,15
SAE		30

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of its subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)