



## Lubrita Steam Cylinder Oil HS 1500

Semi-synthetic steam-cylinder oil

NS-CYL-4273

Steam-cylinder oils

### Product Description and Benefits

This is a semi-synthetic steam-cylinder oil of a high quality, containing no extra additives. Due to the choice of high quality synthetic and mineral base oils, this oil has the following properties:

- a very good protection against oxidation
- little tendency of forming a carbon-like deposit
- a good natural viscosity index
- a good protection against corrosion
- good anti-wear properties
- a slight tendency to emulsify
- a high flash point

### Application

This oil can be used for lubrication of cylinders and valves in steam engines, which work with overheated and saturated steam. In addition to steam-cylinder applications, these oils may also be used to lubricate some vacuum pumps with high operating temperatures and as a lubricant in low speed gears.

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,917
Viscosity 40 °C	mm <sup>2</sup> /s	1500,00
Viscosity 100 °C	mm <sup>2</sup> /s	57,40
Viscosity Index		84
Flash Point COC	°C	316
Pour Point	°C	-6
Conradson Carbonresidu	%	2,5

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)