



Lubrita Brake Fluid DOT 3

Synthetic brake fluid

ST-BRK-4276

Brake fluids

Product Description and Benefits

A synthetic brake fluid having the following properties:

- a good resistance against ageing
- a very good compatibility with seals and gaskets
- minimal corrosion tendency
- optimal viscosity at low temperatures

Application

Applicable for all hydraulic brake systems with drum or disk brakes requiring a synthetic brake fluid type and where a brake fluid of the type DOT 3 is prescribed.

Lubrita Brake Fluid DOT 3 meets the following performance specifications:

SAE J 1703 (jan 80)

FMVSS DOT 3

Typical Analysis

Property	Unit	Typical Value
Density at 20°C	kg/l	1,030
Viscosity -40 °C	mm ² /s	1300
Viscosity 100 °C	mm ² /s	2,00
Flash Point PM	°C	150
Boiling Point (reflux)	°C	237
Wet Boiling Point	°C	145
pH - 50% in ethanolsolution		10,0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com