



Lubrita Brake Fluid DOT 4

Synthetic brake fluid

ST-BRK-4277

Brake fluids

Product Description and Benefits

A synthetic brake fluid having the following properties:

- a good resistance against ageing
- a very good compatibility with seals and gaskets
- minimal corrosion tendency
- high wet boiling point
- optimal viscosity at low temperatures

Application

Applicable for all hydraulic brake systems with drum or disk brakes requiring a synthetic brake fluid and where a brake fluid of the type DOT 4 is prescribed.

Lubrita Brake Fluid DOT 4 meets the following performance specifications:

SAE J 1703

FMVSS DOT 4

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	1,030
Viscosity -40 °C	mm ² /s	1200
Viscosity 100 °C	mm ² /s	2,30
Boiling Point (reflux)	°C	263
Wet Boiling Point	°C	168
pH - 50% in ethanolsolution		8,0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com