



Lubrita WRF 1000

Wide Range Fluid

ST-VAR-4281

Various Special products

Product Description and Benefits

This is a silicone free moisture displacement product based on pure mineral base oils and very special additives in order to obtain the following properties:

- excellent humidity displacing qualities
- a very good anti-corrosion protection
- good removal properties for mild corrosion from electrical switches
- tremendous penetrating capacity
- almost no stain forming
- very little attack of lacquer, plastics and synthetic rubbers

Application

Because of its composition this oil is excellent suitable as a penetrating fluid in places where stain forming can cause serious damages. At the same time, the oil can perfectly be used as humidity displacing product and corrosion remover in electrical switches and circuits. Moreover, it also secures a quick start of motorcar engines. Due to its special composition this oil really has 1000+1 application possibilities.

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,817
Viscosity 40 °C	mm ² /s	2,54
Viscosity 100 °C	mm ² /s	1,12
Flash Point PM	°C	79
Pour Point	°C	-40

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com