



Lubrita Cooling Fluid 50/50

ST-AFR-4284
Lubrita Antifreeze

Product Description and Benefits

An automotive coolant based on monoethyleneglycol and demineralized water with addition of additives to obtain the following properties:

- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behaviour towards seals, gaskets and hoses
- a very good resistance against formation of foam

Application

This coolant may be used all the year round in the cooling-systems of gasoline- and diesel engines. The coolant is ready for use and protected against freezing down to -38 °C.

Lubrita Cooling Fluid 50/50 meets the following performance specifications:

Meets the requirements of
BS 6580:2010

Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	1,080
pH - value		8,1
Reserve alkalinity	ml	11,5
Crystallizationpoint	°C	-38

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com