



Lubrita Marine oil SAE 20W50

NS-CVL-4058

An advanced universal multigrade engine oil

Marine engine oils

Product Description and Benefits

Lubrita Marine oil SAE 20W50 is an advanced high performance SAE 20W-50 multigrade diesel engine oil specially designed and formulated for high performance diesel engines operating in fishing and other marine activities. This engine oil has the following properties:

- Very good control of oil consumption.
- Excellent soot dispersancy, reduce soot induced oil thickening and associated engine wear especially in continuous long-hour services of marine fishing boats.
- Excellent TBN maintenance effectively neutralizing the acidic by-products of combustion
- Reinforced thermal stability.
- Extended antifriction and engine cleaning properties.

Application

Its advanced additives system ensure excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and superior oxidation stability. It also provide excellent resistance to bore polishing, a high level of wear protection and ensure superior engine cleanliness even when operated at extreme operating condition.

Lubrita Marine oil SAE 20W50 meets the following performance specifications:

API CF-4/SL ACEA E2/96 MB228.1 MAN 271

Exceeds major Japanese, American, and European OEMs Specification.

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,890
Viscosity 40 °C	mm²/s	190,00
Viscosity 100 °C	mm²/s	20,00
Viscosity Index		122
Flash Point COC	°C	230
Pour Point	°C	-24
Total Base Number	mgKOH/g	12,0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of Lubrita Europe B.V. or one of it's subsidaries.

web page: www.lubrita.com e-mail: info@lubrita.com