



Lubrita Unifleet Turbo SAE 20W50

An advanced universal multigrade engine oil

NS-CVL-4057

Heavy duty diesel engine oils

Product Description and Benefits

Lubrita Unifleet Turbo SAE 20W50 is blended from highly refined base stocks and specially selected additives to meet special characteristics and performance levels, like excellent thermal and oxidation stability, protection against rust, corrosion and wear. This engine oil has the following properties:

- Very good control of oil consumption.
- Excellent Fuel economy and better cold starting.
- Superior Catalyst and Turbo/Multivalve compatibility.
- Reinforced thermal stability.
- Extended antifriction and engine cleaning properties.
- Very effective control over wear, rust and corrosion.

Application

Lubrita Unifleet Turbo SAE 20W50 oil is recommended for use in diesel and gasoline engines operating over wide range of temperatures throughout the year.

Lubrita Unifleet Turbo SAE 20W50 meets the following performance specifications:

API CF-4/SJ ACEA E7/A3/B-4 MB228.8/229.1 MAN3275 VOLVO VDS3 MTU2.0

MACK EOM PLUS CUMMINS 20076/77/78 CAT ECF-1-a

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,890
Viscosity 40 °C	mm ² /s	179,90
Viscosity 100 °C	mm ² /s	18,50
Viscosity Index		120
Flash Point COC	°C	228
Pour Point	°C	-24
Total Base Number	mgKOH/g	10,0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of Lubrita Europe B.V. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com