



Lubrita Antol 24

Powerful emulsifiable degreaser

ST-CLN-5013

Industrial Cleaners

Properties

All purpose solvent degreaser formulated with strong fast acting emulsifiers. Antol 24 has a flash point $> 62^{\circ}\text{C}$. and is capable of absorbing 4 to 5 times it's volume in lubricants, grease, tar and bitumen. Optimum dissolving performance. Formulated with strong fast acting emulsifiers. Antol 24 becomes whitecoloured (like milk) when mixed with water.

Application

Cleaning and degreasing of machine spare parts, sheet metal work, filters, brushes, paint rollers, floors and storage tanks. Especially suitable for use in general industry such as workshops and factories, as well as shipping industry, agriculture, aviation, petrochemical industry, process-industry and printing industry.



Directions for use

Part Cleaning: Apply pure product by using a brush, cloth or part cleaning equipment. De-Waxing (deparaffining): In high pressure cleaners 1-2% dilution. Preferred temperature $60-80^{\circ}\text{C}$. Apply evenly on the car and rinse with clean water under high pressure. Pressure Cleaning: In high pressure equipment 1-2% dilution. Preferred temperature $60-80^{\circ}\text{C}$. Apply evenly on the surface and rinse with clean water (medium / high pressure). Tank Cleaning: Spray Method - In high pressure equipment 1-2% dilution. Preferred temperature $60-80^{\circ}\text{C}$. Apply evenly on the surface and rinse with clean water (medium / high pressure). Recirculation Method – Preferably dilute 2-6%. Prepare pre-mix in tank near pump room. Usually 3 tanks can be cleaned with one solution after which a fresh solution should be made and heated before cleaning can continue. After cleaning treatment rinse tanks thoroughly with sea water or fresh water.

Environment & Safety

Repeated exposure may cause skin dryness. Keep out of the reach of children. Preferably wear suitable protective clothing and gloves.

Product Features

- Flashpoint $> 62^{\circ}\text{C}$
- Formulated with strong fast acting emulsifiers
- Can be used manually but also extremely suitable if used with high pressure equipment
- Has characteristic scent

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.