



## Lubrita DEO HPX 20W-50

An advanced universal multigrade engine oil

NS-CVL-4046

*Heavy duty diesel engine oils*

### Product Description and Benefits

An advanced universal multigrade engine oil produced with special selected solvent refined base oils and additives. This engine oil has the following properties:

- a very good detergency prevents deposits in the engine
- a very good dispersion that prevents from precipitation and sludge
- a powerful action against wear, corrosion and foam
- a stable viscosity index
- suitable for extended drain intervals
- low ash contents

### Application

This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. Under optimal conditions extended oil drain intervals (up till 30.000 km) are possible, according to instructions of engine manufacturers. This motor oil is also suitable for application in EURO 2 engines and in mixed fleets.

**Lubrita DEO HPX 20W-50 meets the following performance specifications:**

API CH-4/SJ

ACEA A3/B3, E2

### Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,889
Viscosity -15 °C	mPa.s	7600
Viscosity -10 °C	mPa.s	3800
Viscosity 40 °C	mm²/s	154,30
Viscosity 100 °C	mm²/s	17,30
Viscosity Index		122
Flash Point COC	°C	226
Pour Point	°C	-30
Total Base Number	mgKOH/g	10,0
Sulphate Ash	%	1,22

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)