



Lubrita DEO HDM 40

High quality solvent refined base engine oil

ST-CVL-4048

Heavy duty diesel engine oils

Product Description and Benefits

This motor oil is produced with high quality solvent refined base oils and a number of additives, to obtain the following properties:

- a high detergency and dispersion power
- a strong resistance against oxidation
- effective in preventing from wear, corrosion and foam

Application

Suitable lubricating oil for gasoline engines under light service conditions, more over for the diesel engines of passenger cars and for light delivery vans in light service. Not applicable for turbo-charging diesel engines, for which a minimum API CD or a Mil-L-2104C/D level oil is required.

Lubrita DEO HDM 40 meets the following performance specifications:

API SF/CC CCMC G2/D1 MIL-L-46152 B/C Ford M2C153-C (SF/CC) Ford M2C9011-A GM 6085M

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,892
Viscosity 40 °C	mm ² /s	152,00
Viscosity 100 °C	mm ² /s	15,00
Viscosity Index		97
Flash Point COC	°C	245
Pour Point	°C	-12
Total Base Number	mgKOH/g	3,6
Sulphate Ash	%	0,55

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com